



Eslabón rápido de unión Nemag

Información del producto

The Nemag Quick Release Link has been balanced and perfected to become the most reliable, quickest and safest coupling method for ropes and chains. The contact surface of the C-section has been hardened, which considerably lengthens the life span. The construction of the locking piece ensures reliable functioning; even under severe circumstances. The locking pieces are interchangeable.

Optional: Nemag also supplies a key especially designed for the Quick Release Link. This key has a hexagonal head that fits into the keyhole of the locking piece. The horizontal handle provides sufficient grip to be able to open or close any locking piece with one short movement. The sharp end of the handle can be used to remove dirt on the outside (of the keyhole).

Marcado: According to standard, CE-marked

Certificación: EN 1677-1

Referencia CYE	Código	Fuerza máxima de utilización WLL	Fuerza mínima de rotura MBL	Peso kg
Y6AHAMRAP004	RL-4	3	25	0,9
Y6AHAMRAP005	RL-5	4,5	33	1,2
Y6AHAMRAP006	RL-6	5	37,5	1,5
Y6AHAMRAP007	RL-7	7	49	2
Y6AHAMRAP008	RL-8	8	54	2,5
Y6AHAMRAP009	RL-9	9,5	60	3,1
Y6AHAMRAP010	RL-10	12	75	4,4
Y6AHAMRAP011	RL-11	15	95	5,7
Y6AHAMRAP012	RL-12	17	110	7,2
Y6AHAMRAP013	RL-13	21	135	8,7
Y6AHAMRAP014	RL-14	26	160	11
Y6AHAMRAP015	RL-15	30	175	13,5
Y6AHAMRAP017	RL-17	42,5	260	23

Plano

